

R-1005 Rotary Evaporator

ALL TH

Electronic stepless speed regulation, operate stably Corrosion resistance and long service life

R-1005旋转蒸发仪

电子无级调速,运行平稳 回收率高,耐腐蚀,使用寿命长

& whatsapp:+86-13783661974 & :+86-371-67447888 & :+86-371-67447999 Q :www.rotovap.cn @ :rotovap@lanphan.com

PRODUCT DESCRIPTION 产品描述

R-1005 rotary evaporator adopts stepless speed regulation to make glass rotary flask rotate in a constant speed, material formed a large area of balanced thin film, then the rotating flask is uniformly heated by digital thermostat water bath, evaporated under vacuum condition in a high speed, solvent steam is cooled through high efficient glass condenser and recycled to receiving flask. R-1005 rotary evaporator is a new type rotovap of our company, we have four types for your choice: 5L, 10L, 20L, 50L.

R-1005 rotary evaporator inherit the advantages of RE-1002 rotary evaporator, besides, it has new breakthrough:

1. Vacuum manometer displays real time vacuum degree, oil meter is shockproof.

2. Check valve control, continuously charging, it can be vacuum switched in working condition.

3. All valves use newest hand wheel valve, good sealing, operation is more convenient.

4. Water bath is electric lifting, lifting part uses reducing reinforcement motor, lifting process is more stable.

5. Over temperature protection function, when actual temperature exceed 5C° of the setting temperature, machine will automatic power off.

6. If sudden power lost during operation, when reconnect the power, it will stop heating automatic.

R-1005旋转蒸发仪是用无级调速使玻璃旋转瓶恒速旋转,物料在瓶壁形成大面积均匀薄膜,再由智能恒温水浴锅对旋转瓶 进行均匀加热,在真空条件下高速蒸发,溶媒蒸气经高效玻璃冷凝器冷却,回收于收集瓶。R-1005是我公司新款旋转蒸发仪, 有5L,10L,20L,50L四款可供选择。

R-1005旋转蒸发仪在继承RE-1002优良性能的基础上,又有了新的突破,主要表现在:

1. 真空压力表显示实时真空,油性表具有防震动特性。

2. 止回阀控制,可连续放料,机器在工作状态下可进行真空切换。

3. 所有阀门采用最新式一体手轮阀, 密封性好, 操作更为简单方便。

4. 浴锅电动升降, 升降部分采用减速增力电机, 升降过程中更平稳。

5. 超温安全保护功能,当实际温度超过设定温度5C°时,机器加热就会自动断电。

6. 机器工作途中如果突然断电,再次接通电源时,机器会自动停止加热。

DETAILS DRAWING 零件详图



PRODUCT PARAMETER 产品参数

Туре		
型号	R-1005	
Optimmum Ambient Temperature(℃) 最佳环境温度 (℃)	5~35	
Powen(V/Hz) 电源(V/Hz)	(220V/50Hz,220V/60Hz,110V/50Hz) Single Phase (220V/50Hz,220V/60Hz,110V/50Hz) 单相	
Main Engine Speed Regulation 主机调速	Digital Display DC stepless speed regulation 数显 变频无极调速	
Main Engine Roaty Speed(rpm) 主机转速(rpm)	5-120	
Rotary Motor Power(w) 旋转电机功率(W)	30	
Temperature Control(°C) 温度控制(°C)	Digital display temperature control,normal temperature-180 数显控温,0-400℃	
Heating Temperature(°C) 加热温度(°C)	RT-250°C 室温-250°C	
Max vacuum degree(Pa) 最大真空度(Pa)	399.9Pa (under 3 mmHg) 399.9Pa (3mmHg以下)	
Rotary Flask(L) 旋转瓶(L)	5L ¢ 50 flange port 5L ¢ 50法兰口	
Receiving Flask(L) 收集瓶(L)	3	
Condenser Tube 冷凝管	Vertical double-layer snakelike coiler 立式双层蛇形盘管	
Evaporative Capacity(L/h) 蒸发能力(L/h)	water≥ 2 水≥2 ethyl alchol≥4 乙醇≥4	
Water Bath Material 水浴锅材质	Stainless Steel 304 (Covered with Silicone Rubber Case) 不锈钢304(外包硅胶套)	
Water Bath Size(mm) 水浴锅尺寸(mm)	¢280*170	
Lifting Function 升降功能	Electric Lifting 电动升降	
Lifting Motor(W) 升降电机(W)	20	
Lifting Distance(mm) 升降行程(mm)	0~140	
Machine Power(KW) 整机功率(KW)	2.2	
Overall Dimension(mm) 外形尺寸()	765*400*1070	

PRODUCT DETAILS 细节优点



Vacuum Meter _{真空计}

Special designed vacuum meter, high precision and good quality. 特殊订制真空表,精度高,产品质量有保证。



Condenser Tube ^{冷凝管}

Main condenser and auxiliary condenser structure, double backflow snakelike condenser increased cooling area and promote cooling efficiency

凝器采用主冷凝+副冷凝结构,内部采用特制的双 回流蛇形冷凝盘管,增加冷却面积,提高冷却效 率。





LCD screen display both temperature and rotating speed, operation is simple and convenient.

大屏液晶数显,温度转速双数显,操作简单便捷。



Flange connection _{连接法兰}

Flange connection make it easy to dismount, high fastening strength. 各部件之间采用特制的法兰连接,拆装方便,紧固 强度高。

MATCHING PRODUCTS 配套产品



SERIES PRODUCTS 系列产品



RE-52A

RE-100Pro

RE-301







R-1050

RE-2002

RE-5003

QUALITY CERTIFICATION 品质认证









This system is valid for the Sales of Valves, pipe fittings, rubber products, plastic products, metal products, glassware, water treatment equipment, stainless steel products, children's toys, needles textiles, mechanical and electrical products, amusement equipment, building materials, machinery equipment, hardware tools; Design and construction of anti-corroson insulation engineering, municipal engineering, highway engineering; Construction labor subcontracting; Electromechanical equipment installation engineering; Installation of water and electricity; Integrated wiring system engineering; Installation and maintenance of computer; Technical development, technology transfer and technical consultation of computer software; Technical development of photolectric integration; Property services; Cleaning services

Date of issue: Jan. 09, 2018 Date of expiry: Jan. 08, 2021

This certificate will not remain valid only if the certified organization accepts at least one surveillance audit annually within the validity period of the certificate in which the surveillance audit conforming mark is in the designated position on the certificate.



CUSTOMERS FROM VARIOUS COUNTRIES 各国客户



FACTORY SITUATION 工厂情况











Type 型号	R-1005
Package Size(mm) 包装尺寸(毫米)	765*400*1070
Weight(kg) ^{重量(kg)}	70





PACKAGING:

Cartons + wooden cases
Custom packaging is available.

打包:

1.纸箱+木箱。 2.可以提供定制包装。


SHIPMENT:

1.We can deliver the goods to you by international express, such as DHL, UPS, TNT, EMS and so on.

2.You can also choose the right one according to the schedule and budget.3.You may choose to use your own shipping agent.

运输:

1.我们可以通过国际快递将货物运送给您,如DHL,UPS,TNT,EMS等。 2.您还可以根据时间表和预算选择合适的一个。 3.您可以选择使用自己的运输代理商。



1. ASK: What factor decides the working efficiency of Rotary Evaporator

Answer:For same type equipment, mainly includes: steam temperature, vacuum degree and cooling water temperature. Restricted by some material's thermolability, the steam temperature may have certain limitation when working, so high vacuum degree and low cooling water temperature are two main factors for efficiency improving (can select cryopump to lower the temperatur)

2. ASK: How about the anti-explosion ability of R series Rotary Evaporator?

Answer: Our company's Rotary Evaporator adopt alternating current dynamo, stepless speed regulating (or frequency control), no electric brush and no sparkin operation. Water bath kettle which goes with the evaporator adopts nitrogen-sealed relay control, silicon-controlled contactless switch and vacuum switch. Manual control switch adopt twice circuit control which make electric current less than 3mA and has favorable anti-explosion feature

3. ASK: What's the feature of rotary evaporator comparing to other evaporators?

Answer: It has the advantage of small structure, efficient, easy to observe and no metal ion pollution. It is applicable for laboratory, production and valuable material extraction. Its leakproofness ability can compare favorably with foreign equipment while it remain improvement in appearance and humanization design.

1.、问:影响旋转蒸发器效率的因素主要有哪些?

答:就同一规格机器而言,主要有:蒸汽温度、真空度和冷却水温。受某些物料不耐热性的制约,工作时 不可能无限提高蒸汽温度,故高真空度和低冷却水温是提高效率的二大主要因素(可选用低温泵,降低 水温)。

2、问:R系列蒸发器的防爆性如何? 答:我厂生产的旋转蒸发器采用交流电机,无级调速(或变频调速),无电刷,运转中无火花。与之相配的水浴锅控制分别采用充氮密封继电器,可控硅无触点开关,真空开关。手动控制开关采用二次线路控制,控制电流小于3mA,有良好的防爆特性。

3、问:旋转蒸发仪与其他类型蒸发仪相比如何?

答: 它的主要优点是结构小巧, 紧凑高效, 工作直观, 无金属离子污染。适用于实验室、生产中试及名贵物料的提取。其密封性能可与国外的机器相媲美, 但在外观和人性化设计上还有待改进。



PLEASE CONTACT US

Henan Lanphan Industry Co., Ltd

& whatsapp:+86-13783661974 & :+86-371-67447888 & :+86-371-67447999 C :www.rotovap.cn @ :rotovap@lanphan.com