

RE-3002 Rotary Evaporator

Using PTFE and rubber composite seal with high recovery Corrosion resistance and long service life



PRODUCT DESCRIPTION 产品描述


RE-3002 rotary evaporator's rotary bottle maximum capacity is 30L, receiving bottle's maximum capacity is 20L, rotate speed is 0-90r.p.m, motor power is 250W. RE-3002 rotary evaporator(evaporating bottle volume>10L) is equipped with double condenser(main and vice condenser), which has better condensation effect and higher recovery rate. Because this rotary evaporator works under vacuum condition, and contact segment all adopt high temperature resistance material-high borosilicate glass and PTFE material, it is especially suitable for heat reactive material and material which is corrosive to stainless steel's concentration, crystallization, separation and solvent recovery.

The rotary evaporator has advantages of large contact area, high evaporation efficient, easy to handle, low noise, good sealing performance, complete in specifications and can manage easily foam material. It already has various specification products: 2L, 3L, 5L, 10L, 20L, 30L, 50L, 100L and so on, and the 100L rotary evaporator is an exclusive research and developed large-size rotary evaporator of our company, designed for the purpose of mass production need.

RE-3002旋转蒸发仪旋转瓶最大容量30L,收集瓶容量20L,转速0-90r.p.m,电机功率250W。RE-3002旋转蒸发仪(蒸发瓶容 量在10升以上)配备双冷凝器(主冷、副冷)冷凝效果更佳,回收率更高。由于本仪器是在真空条件下工作,且与物料接触部分 全部采用耐高温高硼硅玻璃和聚四氟乙稀材料,所以本仪器特别适用于对热敏感性物料及对不锈钢等金属材料有腐蚀的物 料的浓缩、结晶、分离、溶媒回收。

本仪器接触面积大、蒸发效率高、使用方便、噪音低、密封可靠,可处理易发泡物料,且规格齐全,已形成2L、3L、5L、10L、 20L、30L、50L、100L等多种规格产品,100L旋蒸是本厂独家研发推出的大型旋蒸,便于客户在实际大规模生产中的需要。

DETAILS DRAWING 零件详图



PRODUCT PARAMETER 产品参数

Type 型号	RE-3002	
Glass Material 玻璃材质	GG-17	
Support Material 支架材质	Stainless steel 不锈钢	
Shell Material 锅壳材质	Antiseosis Plastic Spraying 710*620*700mm 喷塑防腐 710*620*700mm	
Inner Container Material 锅胆材质	Stainless steel 500*280mm 不锈钢 500*280mm	
Baseborad Size 底板尺寸	474*474mm	
Volume of Ritary Bottle 旋转瓶容积	30L ¢125 flange port 10L ¢125 法兰口	
Volume of Recycling Bottle 收集瓶容积	20L ¢ 60 flange port 5L ¢ 60 法兰口	
Vacuum Degree 真空度	0.098Mpa	
Rotating Power 旋转功率	180W 220V/50Hz	
Rotating Speed 旋转速度	0-110rpm	
Heating Power 加热功率	8KW 380V/50Hz	
Temperature Control Range of Bath Kettle 浴锅控温范围	0-400°C	
TemperatureAccuracy 控温精度	±1°C	
Up and Down distanc 升降行程	180mm	
Shape Size(mm) 外形尺寸(mm)	970*480*1950mm	
Package Size(mm) 包装尺寸(mm)	1450*390*440 1150*840*660 790*730*790 1.34m ³	
Package Weight(KG) 包装重量(kg)	170	

PRODUCT DETAILS 细节优点



Water Bath ^{浴锅}

Intelligent digital display lifting water and oil universal bath, stainless steel one-time forming liner without welding, annular heating tube heating evenly, heating rate is fas

智能数显升降型水油通用浴锅,不锈钢一次成型 内胆无焊接,环形加热管加热均匀,升温速率快



Condenser Tube ^{冷凝管}

borosilicate glass one - time forming high - efficiency serpentine condensing tube,good condensing effect and high recover 高硼硅玻璃一次成型高效蛇形冷凝管,冷凝效果 好,回收率高



Motor 电机

High quality stainless steel prow,frequency contro 优质不锈钢机头,变频调速



Discharging Valve _{放料阀}

Full PTFE discharge valve, no material
completely free of pollutionPTFE组合旋转密封,有效保持系统的高真空度

MATCHING PRODUCTS 配套产品



RE-3002 Rotary Evaporator RE-3002 旋转蒸发仪



DLSB cooling pump DLSB 制冷泵

SHZ-95B Vacuum Pump SHZ-95B 真空泵

Rotary Vane Vacuum Pump YH Diaphragm Vacuum Pump 旋片式真空泵

YH隔膜真空泵

SERIES PRODUCTS 系列产品



RE-52A

RE-100Pro

RE-301







R-1050

RE-2002

RE-5003

QUALITY CERTIFICATION 品质认证









This system is valid for the Sales of Valves, pipe fittings, rubber products, plastic products, metal products, glassware, water treatment equipment, stainless steel products, children's toys, needles textiles, mechanical and electrical products, amusement equipment, building materials, machinery equipment, hardware tools; Design and construction of anti-corroson insulation engineering, municipal engineering, highway engineering; Construction labor subcontracting; Electromechanical equipment installation engineering; Installation of water and electricity; Integrated wiring system engineering; Installation and maintenance of computer; Technical development, technology transfer and technical consultation of computer software; Technical development of photolectric integration; Property services; Cleaning services

Date of issue: Jan. 09, 2018 Date of expiry: Jan. 08, 2021

This certificate will not remain valid only if the certified organization accepts at least one surveillance audit annually within the validity period of the certificate in which the surveillance audit conforming mark is in the designated position on the certificate.



CUSTOMERS FROM VARIOUS COUNTRIES 各国客户



FACTORY SITUATION 工厂情况











Type 型号	RE-3002	
Package Size(mm) 包装尺寸(毫米)	1450*390*440 1150*840*660 790*730*790 1.34m ³	
Weight(kg) ^{重量(kg)}	170	





PACKAGING:

Cartons + wooden cases
Custom packaging is available.

打包:

1.纸箱+木箱。 2.可以提供定制包装。


SHIPMENT:

1.We can deliver the goods to you by international express, such as DHL, UPS, TNT, EMS and so on.

2.You can also choose the right one according to the schedule and budget.3.You may choose to use your own shipping agent.

运输:

1.我们可以通过国际快递将货物运送给您,如DHL,UPS,TNT,EMS等。 2.您还可以根据时间表和预算选择合适的一个。 3.您可以选择使用自己的运输代理商。



1. ASK: What factor decides the working efficiency of Rotary Evaporator

Answer:For same type equipment, mainly includes: steam temperature, vacuum degree and cooling water temperature. Restricted by some material's thermolability, the steam temperature may have certain limitation when working, so high vacuum degree and low cooling water temperature are two main factors for efficiency improving (can select cryopump to lower the temperatur)

2. ASK: How about the anti-explosion ability of R series Rotary Evaporator?

Answer: Our company's Rotary Evaporator adopt alternating current dynamo, stepless speed regulating (or frequency control), no electric brush and no sparkin operation. Water bath kettle which goes with the evaporator adopts nitrogen-sealed relay control, silicon-controlled contactless switch and vacuum switch. Manual control switch adopt twice circuit control which make electric current less than 3mA and has favorable anti-explosion feature

3. ASK: What's the feature of rotary evaporator comparing to other evaporators?

Answer: It has the advantage of small structure, efficient, easy to observe and no metal ion pollution. It is applicable for laboratory, production and valuable material extraction. Its leakproofness ability can compare favorably with foreign equipment while it remain improvement in appearance and humanization design.

1.、问:影响旋转蒸发器效率的因素主要有哪些?

答:就同一规格机器而言,主要有:蒸汽温度、真空度和冷却水温。受某些物料不耐热性的制约,工作时 不可能无限提高蒸汽温度,故高真空度和低冷却水温是提高效率的二大主要因素(可选用低温泵,降低 水温)。

2、问:R系列蒸发器的防爆性如何? 答:我厂生产的旋转蒸发器采用交流电机,无级调速(或变频调速),无电刷,运转中无火花。与之相配的水浴锅控制分别采用充氮密封继电器,可控硅无触点开关,真空开关。手动控制开关采用二次线路控制,控制电流小于3mA,有良好的防爆特性。

3、问:旋转蒸发仪与其他类型蒸发仪相比如何?

答: 它的主要优点是结构小巧, 紧凑高效, 工作直观, 无金属离子污染。适用于实验室、生产中试及名贵物料的提取。其密封性能可与国外的机器相媲美, 但在外观和人性化设计上还有待改进。



PLEASE CONTACT US

Henan Lanphan Industry Co., Ltd

& whatsapp:+86-13783661974 & :+86-371-67447888 & :+86-371-67447999 C :www.rotovap.cn @ :rotovap@lanphan.com